

ALPHKUT® SMART PLUS [AS-400D]

- Automatic output adjustment dependent on tissue impedance.
- Isolated RF outputs of both monopolar & Bipolar.
The system memory offers 10 user defined programs, plus a preset SUPPLIED program.
- Latest Micro-controller based technology used which is upgrade in features.
- Two Bipolar outputs.
- Memorization of the last operating condition.
- portable and user friendly design.
- Lesser charring and drag.
- Maximum output is 400 cutting.
- Endocut function for polyp cutting



DEVICE

Part No.	Description
AS-400D	Alphkut® Smart Plus Digital [Electrosurgical Unit] With All Its Standard Accessories 400W (Monopolar & Bipolar)

SUPPLIED ACCESSORIES

Part no.	Description
SSP-02	SS Patient plate
PPC-02	Patient plate cable
FSC-03-AS	Tri Pedal Footswitch
MCH-01	Monopolar chuck handle
MC-03	Mains Cord

TECHNICAL DATA

Monopolar cut

Pure cut	400 Watt	500 OHM	1.5 CF
Blend I	300 Watt	500 OHM	2.0 CF
Endocut	99 Watt	500 OHM	1.5 CF

Monopolar coag

Spray	120 Watt	500 OHM	7.0 CF
Force	150 Watt	500 OHM	6.0 CF
Dessicate	150 Watt	500 OHM	5.0 CF

Bipolar

Micro	70 Watt	100 OHM	1.5 CF
Macro	90 Watt	100 OHM	1.5 CF
Program	10		

Power supply	170 - 260 VAC
Frequency	50 Hz
Maximum power	400W
Classification	Protection Class 1, type Bf
Dimension (w x h x d)	300 x 130 x 365 mm
Weight	8kg

SS Patient plate
SSP-02



Patient plate cable
PPC-02



Tri Pedal Footswitch
FSC-03-AS



Mains cord
MC-03



Monopolar chuck handle
MCH-01



*Bipolar cable
BCS-04-03-VMF



*Open bipolar tweezer
OBT-07



*Silicon Patient plate
SPP-02

